



## SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

CHEMITOX, INC.,  
YAMANASHI TESTING CENTER KAI  
18349 Egusa, Sutama-cho  
Hokuto-shi, Yamanashi-Ken, Japan

Mr. Yuji Kamiya (Authorized Representative) Phone: 81 551 42 5061 email:yu-kamiya @chemitox.co.jp  
Mr. Kiyo hiko Sakamoto (Deputy Authorized Representative) email: k-sakamoto@chemitox.co.jp  
Webpage: <https://www.chemitox.co.jp>

### MECHANICAL

Valid To: July 31, 2024

Certificate Number: 1136.03

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following mechanical tests on the following materials/products: Photovoltaic Modules; Adhesives and Sealants; Varnish; Industrial Laminate; Ceramics; Films and Packaging; Leather; Packaging and Containers; Paper, Paperboard and Pulp; Plastics and Polymers; Rubber and Rubber Products; Textiles; Information Technology Equipment (ITE); Printed Wiring Board; Magnet Wire; and Wire Positioning Devices.

#### Test:

#### Test Method(s)<sup>1</sup>:

Tensile Strength Test

ASTM D412, D638, D882; UL 746A (Sections 10-12);  
CAN/CSA C22.2 No.0.17 (Section 5.5);  
ISO 527-1, 527-2, 527-3, 527-4, 527-5;  
JIS K6911, K7127, K7161-1, K7161-2, K7164, K7165

Flexural Strength Test

ASTM D790; CAN/CSA C22.2 No.0.17 (Section 5.4);  
ISO 178; JIS K7171; UL 746A (Section 16)

Tensile Impact Test

ASTM D1822; JIS K7160; CAN/CSA C22.2 No.0.17 (Section 5.7);  
UL 746A (Section 14); ISO 8256

Ball Pressure Test

CAN/CSA C22.2 No.0.17 (Section 9.6);  
Electrical Appliance and Materials Safety Law (in Japan 3-31-86);  
UL 746C (Section 62); IEC 60695-10-2; JIS C 60695-10-2;  
IEC 60335-1 (Section 30)

Izod Impact

ASTM D256; JIS K7110, JIS K6911 (Section 5.21);  
ISO180; UL 746A (Section 13); CSA C22 No.17 (Section 5.3)

Charpy Impact Testing

ASTM D6110, JIS K7111-1, JIS K6911 (Section 5.20);  
ISO 179-1; UL746A (Section 15); CSA C22 No.17 (Section 5.2)

Heat Deflection Temperature (HDT)

UL746A; ASTM D648; ISO 75-1, 75-2; JIS K7191-1, K7191-2

Vicat Softening Point/Temperature (VST)

UL746A, UL746C; ASTM D1525;  
ISO 306; JIS K7206

<u>Test:</u>	<u>Test Method(s)<sup>1</sup>:</u>
Relative Thermal Endurance Index (RTE, RTI)	IEC 60216-5, 61730-1; UL 746B; JIS C61730-1
20 mm Flame Confirmation Test	ASTM D5207; IEC 60695-11-4
125 mm Flame Confirmation Test	ASTM D5207; IEC 60695-11-3
12 mm Flame Confirmation Test	IEC 60695-11-5; GB/T 5169.5
Horizontal Burning Test	ASTM D635; CAN/CSA C22.2 No.0.17 (Section 4.2.3); CAN/CSA C22.2 No.60950-1 (Sections 4.7.3.1 - 4.7.3.6); EN 60950-1 (Sections 4.7.3.1 - 4.7.3.6); IEC 60950-1 (Sections 4.7.3.1 - 4.7.3.6), IEC 60695-11-10; JIS K6911; UL 94 (Section 7); UL 60950-1 (Sections 4.7.3.1 - 4.7.3.6); GB/T 5169.16, GB 4943.1, (Sections 4.7.3.1-4.7.3.6); BS EN 60695-11-10
Thin Material Vertical Burning Test	ASTM D4804; CAN/CSA C22.2 No.0.17 (Section 4.2.4); ISO 9773; UL 94 (Section 11)
Vertical Burning Test	ASTM D3801; CAN/CSA C22.2 No.0.17 (Section 4.2.2); CAN/CSA C22.2 No.60950-1 (Sections 4.7.3.1 - 4.7.3.6); EN 60950-1 (Sections 4.7.3.1 - 4.7.3.6); IEC 60950-1 (Sections 4.7.3.1 - 4.7.3.6), IEC 60695-11-10; JIS K6911; UL 94 (Section 8); UL 60950-1 (Sections 4.7.3.1 - 4.7.3.6); GB/T 5169.16, GB 4943.1, 4.7.3.1-4.7.3.6; BS EN 60695-11-10
Vertical Burning Test using a 125 mm Flame Source	UL 94 (Section 9), UL 60950-1, (Sections 4.7.3.1-4.7.3.6); IEC 60695-11-20; ASTM D5048; EN 60950-1, (Sections 4.7.3.1-4.7.3.6); CAN/CSA C22.2 No.0.17 (Section 4.2.1), CAN/CSA C22.2 60950-1, (Sections 4.7.3.1-4.7.3.6)
Vertical Burning Rate of Materials Test	UN ECE R118 (Annex 8)
Horizontal Burning Foamed Material Test	UL 94 (Section 12); CAN/CSA C22.2 No.0.17 (Section 4.2.5), UL 60950-1 (Sections 4.7.3.1 - 4.7.3.6); ASTM D4986; IEC 60950-1 (Sections 4.7.3.1 - 4.7.3.6); EN 60950-1 (Sections 4.7.3.1 - 4.7.3.6); CAN/CSA C22.2 No.60950-1 (Sections 4.7.3.1 - 4.7.3.6); ISO 9772; GB 4943.1, (Sections 4.7.3.1-4.7.3.6)
Burning Test using a 20 mm Flame Source Used in Electrical Equipment Evaluations	UL 746C (Sections 16 and 51),UL 60950-1 (Annex A2); IEC 60950-1 (Annex A2); EN 60950-1 (Annex A2); CAN/CSA C22.2 No.60950-1 (Annex A2); GB 4943.1, Annex A2

<u>Test:</u>	<u>Test Method(s)<sup>1</sup>:</u>
Burning Test using a 127 mm Flame Source Used in Electrical Equipment Evaluations	UL 746C (Sections 17 and 52), UL 60950-1 (Annex A1); IEC 60950-1 (Annex A1); EN 60950-1 (Annex A1); CAN/CSA C22.2 No.60950-1 (Annex A1); GB 4943.1, Annex A1
Enclosure Burning Test used in Electrical Evaluations	UL 746C (Sections 18 and 53)
Burning Test using a Needle Flame Source	UL 746C (Section 15), UL 60950-1, Annex A2.7, UL 1694; GB/T 5169.5; CAN/CSA C22.2 No.0.17 (Section 9.2.1); IEC 60695-11-5, IEC 60335-1 (Section 30 and Annex E), IEC 60950-1, Annex A2.7; EN 60950-1, Annex A2.7; CAN/CSA C22.2 60950-1, Annex A2.7; GB 4943.1, Annex A2.7; IEC 62368-1 Annex S
Burning Test of Automotive Interior Materials	ASTM D5132; FMVSS 302; ISO 3795; JIS D1201; SAE J369; GB 8410; UN ECE R118 (Annex 6)
Ignitability Test	ISO 11925-2; IEC 61730-2 (MST 24); DIN 4102-1 (Class B2 only), 53438-2, 53438-3; GB 8626; JIS C61730-2 (MST 24)
VW-1 Flammability Test	UL224 (Section, 5.11), UL510 (Section 6), UL510a (Section 9, 20), UL1441 (Section 5.7), UL1581 (Section, 1080), UL2556 (Section, 9.4); ASTM D2671 (Section 72 Procedure C); IEC TS 60695-11-21
Resistance to Flame Propagation Test for Automotive Cables and Wires	UN ECE R118 (Annex10); ISO 6722-1 (Section 5.22)
Test Methods for Rubber or Plastic Insulated Wires and Cables	JIS C3005 (Section 4.26)
Folding Endurance	JIS C5016 (Section 8.7), JIS C6471 (Section 8.2)

<u>Test:</u>	<u>Test Method(s)<sup>1</sup>:</u>
Thermal Shock by Air	JIS C5012 (Section 9.2), JIS C5016 (Section 9.2)
Hot Oil	JIS C5012 (Section 9.3), JIS C5016 (Section 9.3)
Reflow Solder	JIS C5012 (Section 10.4.2)
Cross-Sectional Observation Test	JIS C5012 (Section 6.2), JIS C5016 (Section 6.2), JIS C61730-2 (MST 04); IEC 61730-2 (MST 04)
Vibration	JIS C5402-6-4, JIS C60068-2-6, JIS C60068-2-53, JIS C60068-2-64, JIS C60068-2-80, JIS D1601, JIS C60068-2-57; IEC 60068-2-6, IEC 60068-2-53, IEC 60068-2-57, IEC 60068-2-64, IEC 60068-2-80; ISO 19453-3 (Section 4.1), ISO 16750-3 (Section 4.1); JASO D014-3 (Section 4.1), JASO D902 (Section 6.4), JASO M312 (Section 5.6)
Shock	JIS C60068-2-27, JIS C60068-2-53; IEC 60068-2-27, IEC 60068-2-53; ISO 19453-3 (Section 4.2), ISO 16750-3 (Section 4.2); JASO D014-3 (Section 4.2)

### Testing Performed on Photovoltaic Modules

Visual Inspection	IEC 61730-2 (MST 01), IEC 61215-2 (Section 4.1, MQT 01); JIS C61730-2 (MST 01), JIS C61215-2 (Section 4.1, MQT 01)
Thermal Cycling	IEC 61730-2 (MST 51), IEC 61215-2 (Section 4.11, MQT 11); JIS C61730-2 (MST 51), JIS C61215-2 (Section 4.11, MQT 11)

**Test:****Test Method(s)<sup>1</sup>:****Testing Performed on Photovoltaic Modules (cont'd)**

Humidity Freeze	IEC 61730-2 (MST 52), IEC 61215-2 (Section 4.12, MQT 12); JIS C61730-2 (MST 52), JIS C61215-2 (Section 4.12, MQT 12)
Damp Heat	IEC 61730-2 (MST 53), IEC 61215-2 (Section 4.13, MQT 13); JIS C61730-2 (MST 53), JIS C61215-2 (Section 4.13, MQT 13)
Salt Mist Corrosion	IEC 61701 (Test method 1~7), IEC 60068-2-52 (Test method 1~7); JASO D014-4 (Section 5.5), JASO D616 (Section 6.20), JASO M609-91
Cold Conditioning	IEC 61730-2 (MST 55)
Dry Heat Conditioning	IEC 61730-2 (MST 56)
Cut Susceptibility Test	IEC 61730-2 (MST 12); JIS C61730-2 (MST 12)
Bending Test	IEC 61215-2 (Section 4.22, MQT 22)
Hot Spot Endurance Test	IEC 61730-2 (MST 22), IEC 61215-2 (Section 4.9, MQT 09); JIS C61730-2 (MST 22), JIS C61215-2 (Section 4.9, MQT 09)
Fire Test	IEC 61730-2 (MST 23 Annex B, B.3); UL 790 (Sections 7 and 8), UL 1703 (Section 31) JIS C8993, JIS C61730-2 (MST 23)
Bypass Diode Thermal Test	IEC 61730-2 (MST 25), IEC 61215-2 (Section 4.18.1, MQT 18.1); JIS C61730-2 (MST 25), JIS C61215-2 (Section 4.18.1, MQT 18.1)
Bypass Diode Functionality Test	IEC 61215-2 (Section 4.18.2, MQT 18.2); JIS C61215-2 (Section 4.18.2, MQT 18.2)
Bypass Diode – Thermal Runaway Test	IEC 62979
Module Breakage	IEC 61730-2 (MST 32); JIS C61730-2 (MST 32)

<u>Test:</u>	<u>Test Method(s)<sup>1</sup>:</u>
<b><u>Testing Performed on Photovoltaic Modules (cont'd)</u></b>	
Dynamic Mechanical Load	IEC TS 62782
Static Mechanical Load Test	IEC 61215-2 (Section 4.16, MQT 16), 61730-2 (MST34); JIS C61215-2 (Section 4.16, MQT 16), JIS C61730-2 (MST34)
Stabilization	IEC 61215-2 (Section 4.19, MQT 19);
Stabilization (cont'd)	JIS C61215-2 (Section 4.19, MQT 19)
UV-Xenon Arc Exposure Test	UL 746C; ASTM G155; ISO 4892-2; IEC 61730-1, IEC 62368-1 Annex C
Water Exposure/Immersion	UL 746C (Sections 26 and 58)
Surface Flame Spread Test	ASTM E162; IEC 61730-1 <sup>2</sup> (Edition 1, 2004, Section 5.4.2); ISO 5658-2; IMO Resolution MSC.307(88) – 2010 FTP Code Annex 1: Part 5
<b>Environmental Test</b>	
Visual Inspection	EN50155 (Section 13.4.1); IEC 60571 (Section 12.2.2)
Performance Test	EN50155 (Section 13.4.2); IEC 60571 (Section 12.2.3)
Low Temperature Start-up Test	EN50155 (Section 13.4.4); IEC 60571 (Section 12.2.4)
Dry Heat Test	EN50155 (Section 13.4.5); IEC 60571 (Section 12.2.5)
Low Temperature Storage Test	EN50155 (Section 13.4.6)
Cyclic Damp Heat Test	EN50155 (Section 13.4.7); IEC 60571 (Section 12.2.6)
Salt Mist Test	EN50155 (Section 13.4.10); IEC 60571 (Section 12.2.11)
Smoke Density Measurement	ASTM E662, ASTM F814; ISO 5659-2; 14 CFR Appendix F to Part 25, Part V; FAA Aircraft Materials Fire Test Handbook, Chapter 6 BSS 7239; DIN 5510-2 Appendix D.4 (Colorimetric Measurements)
<b>Toxicity</b>	
Flammability Testing for Aircraft Interior Materials (Vertical, Horizontal, 45-Degree, 60 Degree, Flammability Test)	14 CFR 25 (Appendix F, Part 1); CS 25 (Appendix F, Part 1); JAR 25 (Appendix F, Part 1); JCAB AIM Part III (Appendix F, Part 1); RTCA/DO-160G (Section 26); FAA Aircraft Materials Fire Test Handbook Chapter 1, FAA Aircraft Materials Fire Test Handbook Chapter 2, FAA Aircraft Materials Fire Test Handbook Chapter 3, FAA Aircraft Materials Fire Test Handbook Chapter 4
Test Methods for Determining the Degree of Cure in Ethylene-Vinyl Acetate	TPE-1-21

**Test:****Test Method(d):****Testing Performed on Photovoltaic Modules (cont'd)**

Test to Determine the Melting Behavior      UN ECE R118 (Annex 7)  
of Material

Heat Release Rate (Cone Calorimeter  
Method) and Smoke Production Rate      ISO 5660-1  
(Dynamic Measurement)      ASTM E1354

<sup>1</sup> UL 60950-1, IEC 60950-1, CAN/CSA C22.2 No.60950-1, and EN60950-1 base requirements are nearly identical. Section numbers relate to all four editions, unless otherwise indicated.

<sup>2</sup> This laboratory's scope contains withdrawn or superseded methods. As a clarifier, this indicates that the applicable method itself has been withdrawn or is now considered "historical" and not that the laboratory's accreditation for the method has been withdrawn



## Accredited Laboratory

A2LA has accredited

**CHEMITOX, INC., YAMANASHI TESTING CENTER KAI**  
Yamanashi-ken, JAPAN

for technical competence in the field of

**Mechanical Testing**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017  
*General requirements for the competence of testing and calibration laboratories.* This accreditation demonstrates  
technical competence for a defined scope and the operation of a laboratory quality management system  
(refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 7<sup>th</sup> day of October 2022.

A handwritten signature in blue ink, appearing to read "Trace McInturff".

Mr. Trace McInturff, Vice President, Accreditation Services  
For the Accreditation Council  
Certificate Number 1136.03  
Valid to July 31, 2024

*For the tests to which this accreditation applies, please refer to the laboratory's Mechanical Scope of Accreditation.*